



MKS-NEXGEN-20M

“BE HEARD THE FIRST TIME”



MKS-NEXGEN-20M Specification

Keying	Metal to metal key for positive alignment
Housing Material	316 SS passivated per QQ-P-35 Type VI with naval bronze engaging nut.
Contacts	Contacts gold plated per MIL-G-45204
Threads	Engaging nuts have Acme threads for rugged applications and for quick connection
Voltage	500 VDC
Applications	<ul style="list-style-type: none"> • Light and Heavy Duty applications • Hazardous Environment • Power Transmission • Signal Telemetry • ROV Applications
Surface Finish	32 finish
Appearance	Matte Black
Mating	Knurled Exterior Around Bayonet For Hand Tightening
IP Rating	IP-68, 20 Meter, 2 Hours, Per MIL-STD-810G Method 512.5
Plating	Black Nickel in accordance with MIL-DTL-26074, Grade A

PRODUCTS AVAILABLE TO U.S. AND INTERNATIONAL MARKETS

(845) 278-0960 INFO@TEAHEADSETS.COM FACEBOOK.COM/TEAHEADSETS

16 MOUNT EBO ROAD SOUTH SUITE 6 BOX 404 | BREWSTER, NY 10509

WWW.TEAHEADSETS.COM